



REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图


1. Product main performance/产品主要性能指标:  
 Operating Temperature/工作温度 : -55°C~150°C  
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]  
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:  
 Vibration/振动 : 15g [10Hz~2000Hz]  
 Endurance (Shell)/机械寿命 : 2000+

2. 电气性能  
 Insert Configuration/针芯配置: 1P. 314 14Low Voltage  
 Pin Size/接触件直径:  $\phi 0.5\text{mm}$   
 Contact resistance接触电阻:  $\leq 15\text{m}\Omega$   
 Insulation resistance/绝缘电阻:  $5000\text{M}\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 750V(AC)  
 Rated working current额定工作电流: 2.0A  
 Cable/配接电缆:  $\phi 3.5\text{mm}-\phi 4.5\text{mm}$

Other Specification/其它规格:  
 Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质 : PSU  
 Other Shell Material/其它壳体材质: PSU  
 Insulator material/绝缘体材料: PPS  
 IP Rating/防护等级 : IP50  
 \*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



DRAWN BY: 绘图: PDO3 2024. 05. 28		 美易连电子科技(深圳)有限公司 Meiyilian electronic technology(shenzhen)Co., Ltd.		名称		PAA-1P直式插头(带护套式尾帽)
CHECKED BY: 审核: Z01 2024. 05. 28				PART NAME		PAA-1P Straight Plug (with jacketed tail cap)
APPROVED BY: 核准: PDO3 2024. 05. 28		UNIT: UNT: mm		型号		PAA. 1P. 314. PLAC42GZ
GENERAL TOLERANCE (UNLESS SPECIFIED)		比例 SCALE: 1: 1		PART NAME		
$\leq 10 \pm 0.1$		SIZE: A4		REV/版本		A1
$< 10 \sim \leq 20 \pm 0.15$		SHEET: 1 OF 1				
$< 20 \sim \leq 50 \pm 0.3$		FIRST ANGLE PROJECTION				
AngTe $\pm 1^\circ$						