

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$

Humidity(max)/最大潮湿: $<=95\%$ [at 60 deg C / 140 F]

Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]

Shock Resistance/冲击: 100g[6ms]

Endurance (Shell)/机械寿命: 5000+

Cable/配接电缆: $\phi 4.1\text{mm} - \phi 5.0\text{mm}$

2. 电气性能

Insert Configuration/针芯配置: 1BP. 305 5Low Voltage

Pin Size/接触件直径: $\phi 0.9\text{mm}$

Contact resistance接触电阻: $\leq 9\text{m}\Omega$

Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))

Withstand voltage/耐电压: 1250V(AC)

Rated working current额定工作电流: 9.0A

Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金

Housing Material/外壳材质: PEEK



Other Shell Material/其它壳体材质: 铜镀镍

Insulator material/绝缘体材料: PEEK

IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



view K
K向孔位排列

<p>DRAWN BY: 绘图: P003 2024.03.28</p> <p>CHECKED BY: 审核: Z01 2024.03.28</p> <p>APPROVED BY: 核准: P005 2024.03.28</p>	<p>美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.</p>	<p>单位 UNIT: mm</p>	<p>名称 PART NAME</p>	<p>DWG-1BP浮动式插座 (不带护套式尾帽) DWG-1BP Floating socket (without jacketed tail cap)</p>
<p>GENERAL TOLERANCE (UNLESS SPECIFIED)</p> <p>$\leq 10 \pm 0.1$</p> <p>$< 10 \sim \leq 20 \pm 0.15$</p> <p>$< 20 \sim \leq 50 \pm 0.3$</p> <p>Angle $\pm 1^{\circ}$</p>		<p>FIRST ANGLE PROJECTION</p>	<p>比例 SCALE: 1: 1</p>	
<p>REV/版本</p>	<p>A1</p>	<p>SHEET: 1 OF 1</p>	<p>DHG. 1BP. 305. KWKLD52</p>	