

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: -55°C~150°C

A Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F]

Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾: 96hr


Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]

Shock Resistance/冲击: 100g[6ms]

Endurance (Shell)/机械寿命: 5000+

Cable/配接电缆:  $\phi 5.1\text{mm}-\phi 6.0\text{mm}$



B 2. 电气性能

Insert Configuration/针芯配置: 1BP. 308 8Low Voltage

Pin Size/接触件直径:  $\phi 0.7\text{mm}$

Contact resistance接触电阻:  $\leq 12.5\text{m}\Omega$

Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))

Withstand voltage/耐电压: 950V(AC)

Rated working current额定工作电流: 5.0A

C Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金


Housing Material/外壳材质: PEEK

Other Shell Material/其它壳体材质: 铜镍镍

Insulator material/绝缘体材料: PPS

IP Rating/防护等级: IP50



\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



view K  
K向孔位排列

view K  
K向孔位排列

D

DRAWN BY: 绘图: P003 2024.05.28 CHECKED BY: 审核: Z01 2024.05.28 APPROVED BY: 核准: P005 2024.05.28	 美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.		名称 PART NAME DHG-1BP浮动式插座(带护套式尾帽) DHG-1BP floating socket (with jacketed tail cap)	
GENERAL TOLERANCE (UNLESS SPECIFIED)		 FIRST ANGLE PROJECTION	SIZE: A4 SHEET: 1 OF 1	SHEET: 1 OF 1
$\leq 10$ $\pm 0.1$ $< 10^\circ \leq 20$ $\pm 0.15$ $< 20^\circ \leq 50$ $\pm 0.3$ Angle $\pm 1^\circ$	REV/版本 A1	https://www.mylconnector.com/	https://www.mylconnector.com/	SHEET: 1 OF 1

1

2

https://www.mylconnector.com/

4

5

https://www.mylconnector.com/

7

8