


I. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: $\phi 4.4\text{mm}-\phi 5.3\text{mm}$




2. 电气性能

Insert Configuration/针芯配置: 1BP.314 14Low Voltage
 Pin Size/接触件直径: $\phi 0.5\text{mm}$
 Contact resistance接触电阻: $\leq 15\text{m}\Omega$
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 750V(AC)
 Rated working current额定工作电流: 2.0A

Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



插头前视图
K向孔位排列

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/制图

DRAWN BY: 绘图: P003 2024.05.28 CHECKED BY: 审核: Z01 2024.05.28 APPROVED BY: 核准: P005 2024.05.28		美易连电子科技(深圳)有限公司 Meiyilian electronic technology(shenzhen)Co.,Ltd.	
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^\circ \leq 20^\circ \pm 0.15$ $< 20^\circ \leq 50^\circ \pm 0.3$ Angle $\pm 1^\circ$			单位: mm 名称: TGA-1BP直式插头(不带护套式尾帽) 比例: 1:1 名称: TGA-1BP Straight Plug 型号: TGA.1BP.314.KWKAD58 比例: 1:1 名称: TGA.1BP.314.KWKAD58 型号: TGA.1BP.314.KWKAD58
REV/版本: A1 SHEET: 1 OF 1		名称: TGA-1BP直式插头(不带护套式尾帽) TGA-1BP Straight Plug (without jacketed tail cap) 型号: TGA.1BP.314.KWKAD58	名称: TGA-1BP直式插头(不带护套式尾帽) TGA-1BP Straight Plug (without jacketed tail cap) 型号: TGA.1BP.314.KWKAD58