


## 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度:  $-55^{\circ}\text{C}\sim 150^{\circ}\text{C}$   
 Humidity(max)/最大潮湿:  $\leq 95\%$  [at  $60\text{ deg C} / 140\text{ F}$ ]  
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾: 96hr

### Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]  
 Shock Resistance/冲击: 100g[6ms]  
 Endurance (Shell)/机械寿命: 5000+  
 Cable/配接电缆:  $\phi 2.1\text{mm}-\phi 3.0\text{mm}$




## 2. 电气性能



Insert Configuration/针芯配置: 1BP. 302 2Low Voltage  
 Pin Size/接触件直径:  $\phi 1.3\text{mm}$   
 Contact resistance接触电阻:  $\leq 5\text{m}\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1500V(AC)  
 Rated working current额定工作电流: 15.0A

### Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质: PEEK  
 Other Shell Material/其它壳体材质: 铜镀镍  
 Insulator material/绝缘体材料: PPS  
 IP Rating/防护等级: IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



|   |   |   |   |
|---|---|---|---|
| DRAWN BY:<br>绘图: P003<br>2024.05.28<br>CHECKED BY:<br>审核: Z01<br>2024.05.28<br>APPROVED BY:<br>核准: P005<br>2024.05.28                         |  美易连电子科技(深圳)有限公司<br>Meiyilian electronic technology(shenzhen)Co., Ltd. |   | 名称<br>PART NAME<br>TG-1BP直式插头(带护套式尾帽)<br>TG-1BP Straight Plug<br>(with jacketed tail cap) |
| GENERAL TOLERANCE<br>(UNLESS SPECIFIED)<br>$\leq 10 \pm 0.1$<br>$< 10 \sim \leq 20 \pm 0.15$<br>$< 20 \sim \leq 50 \pm 0.3$<br>Angle $\pm 1'$ | <br>FIRST ANGLE PROJECTION   | 单位<br>UNIT: mm<br>比例<br>SCALE: 1: 1<br>SIZE: A4 | 型号<br>PART NAME<br>TGA. 1BP. 302. KWLAD32Z  |
| REV/版本<br>A1  | SHEET: 1 OF 1   | https://www.myconnector.com/                    |   |