


1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿: $\leq 95\%$ [at 60 deg C / 140 F]
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]
 Shock Resistance/冲击: 100g[6ms]
 Endurance (Shell)/机械寿命: 5000+
 Cable/配接电缆: $\phi 4.4\text{mm} - \phi 5.3\text{mm}$




2. 电气性能

Insert Configuration/针芯配置: IBP.314 14Low Voltage
 Pin Size/接触件直径: $\phi 0.5\text{mm}$
 Contact resistance接触电阻: $\leq 15\text{m}\Omega$
 Insulation resistance/绝缘电阻: $5000\text{M}\Omega$ (测试电压500V(DC))
 Withstand voltage/耐电压: 750V(AC)
 Rated working current额定工作电流: 2.0A


Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PPS
 IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Plug front view
插头前视图



view K
K向孔位排列

| REV/版本 | DESCRIPTION/变更内容 | DATE/日期 | DRAWN BY/绘图 |
|--------|------------------|---------|-------------|
| | | | |

DRAWN BY:
绘图: PDD5 2024.05.28
 CHECKED BY:
审核: Z01 2024.05.28
 APPROVED BY:
核准: PDD5 2024.05.28



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology (shenzhen) Co., Ltd.

| GENERAL TOLERANCE (UNLESS SPECIFIED) | | 单位 UNIT: mm | 名称 PART NAME | DHA-1BP浮动式插座(带护套式尾箱) DHA-1BP Floating socket (with Jacketed tail emp) |
|--------------------------------------|-----------------|---------------------------------|-----------------|--|
| ≤ 10 | ± 0.1 | 比例 SCALE: 1: 1 | 型号 PART NAME | DHA. 1BP. 314. KWLLD58Z |
| $< 10^{\circ} \sim 20$ | ± 0.15 | 第一角投影 FIRST ANGLE PROJECTION | | |
| $< 20^{\circ} \sim 50$ | ± 0.3 | 尺寸 SIZE: A4 | | |
| Angle | $\pm 1^{\circ}$ | REV/版本 A1 | | |
| | | SHEET: 1 OF 1 | | |