REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图

1.Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃～200℃
Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
Salt Spray Corrosion/盐 雾 : 96hr
P op (max)/最大环境压力 : 60 bar (870 psi)

Mechanical data/机械特性:
Vibration/振 动 : 15g[10Hz～2000Hz]
Shock Resistance/冲 击 : 100g[6ms]
Endurance (Shell)/机械寿命 : 5000+





view K
K向孔位排列

2.电气性能
Insert Configuration/针芯配置:00U.305 5Low Voltage
Pin Size/接触件直径:⌀0.4mm
Contact resistance接触电阻:≤20mΩ
Insulation resistance/绝缘电阻:5000MΩ(测试电压500V(DC))
Withstand voltage/耐电压:650V(AC)
Rated working current额定工作电流:1.7A
Cable/配接电缆:⌀2.1mm-⌀3.0mm

Other Specification/其它规格:
Contact PIN/接触体 :Gold-Tin bronze plating/锡青铜镀金
Housing Material/外壳材质 :black chrome plated brass/黄铜镀黑铬
Other metal spare parts/其余金属件 : nickel plated brass/黄铜镀镍
Insulator material/绝缘材料: PPS
IP Rating/防护等级 :IP68(插合状态)
*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

DRAWN BY: 绘图:PD03 2024.05.28 CHECKED BY: 审核:ZO1 2024.05.28 APPROVED BY: 核准:PD05 2024.05.28	MEIYILIAN 美易连	美易连电子科技（深圳）有限公司 Meiyilian electronic technology(shenzhen)Co.,Ltd.	
GENERAL TOLERANCE (UNLESS SPECIFIED) ≤10 ±0.1 10~20 ±0.15 20~50 ±0.3 Angle ±1°	FIRST ANGLE PROJECTION	UNIT: mm SCALE: 1:1 SIZE: A4 SHEET:1 OF 1	名称 PART NAME: TWA-00U弯角插头（带护套式尾帽） TWA-00U Angle Plug (with jacketed tail cap)
REV/版本 A1			型号 PART NAME: TWA.00U.305.KLAD32Z

https://www.mylconnector.com/