

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: ϕ 3.1mm- ϕ 4.0mm



2. 电气性能

Insert Configuration/针芯配置: IBP.314 14Low Voltage
 Pin Size/接触件直径: ϕ 0.5mm
 Contact resistance接触电阻: \leq 15m Ω
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 750V(AC)
 Rated working current额定工作电流: 2.0A


Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEEK
 Other Shell Material/其它壳体材质: 铜电镀
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.




Socket front view
插座前视图




view K
K向孔位排列

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图

DRAWN BY: 绘图: P003	2024.05.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: P005	2024.05.28

	美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.	
	单位 UNITS: mm 比例 SCALE: 1:1	名称 PART NAME

GENERAL TOLERANCE (UNLESS SPECIFIED) \leq 10 \pm 0.1 <10° \leq 20 \pm 0.15 <20° \leq 50 \pm 0.3 Ang Fe \pm 1°	 FIRST ANGLE PROJECTION	尺寸 SIZE: A4 SHEET: 1 OF 1	型号 PART NAME: DHA. IBP. 314. KWKLD42Z
--	---	---------------------------------	--

REV/版本	A1	比例 SCALE: 1:1 尺寸 SIZE: A4 SHEET: 1 OF 1	名称 PART NAME 型号 PART NAME: DHA. IBP. 314. KWKLD42Z
--------	----	---	---

1

2

<https://www.myconnector.com/>

4

5

<https://www.myconnector.com/>

7

8