

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿: $<=95\%$ [at 60 deg C / 140 F]
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]
 Shock Resistance/冲击: 100g[6ms]
 Endurance (Shell)/机械寿命: 5000+
 Cable/配接电缆: $\phi 6.1\text{mm}-\phi 7.0\text{mm}$

2. 电气性能



Insert Configuration/针芯配置: 2BP. 312 12Low Voltage
 Pin Size/接触件直径: $\phi 0.7\text{mm}$
 Contact resistance接触电阻: $\leq 12.5\text{m}\Omega$
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 1250V(AC)
 Rated working current额定工作电流: 7.0A

Other Specification/其它规格:


Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PPS
 IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更项目	DATE/日期	DRAWN BY/绘图



DRAWN BY: 绘图: PDD5		2024.05.28
CHECKED BY: 审核: Z01		2024.05.28
APPROVED BY: 核准: PDD5		2024.05.28
GENERAL TOLERANCE (UNLESS SPECIFIED)		
$\leq 10 \pm 0.1$		
$< 10^{\circ} \sim \leq 20^{\circ} \pm 0.15$		
$< 20^{\circ} \sim \leq 50^{\circ} \pm 0.3$		
Angle $\pm 1^{\circ}$		

 美易连电子科技(深圳)有限公司 Meiyilian electronic technology(shenzhen)Co.,Ltd.		单位 UNIT: mm	名称	DHG-2BP浮动式插座(带护套式尾帽)
		比例 SCALE: 1:1	PART NAME	DHG-2BP Floating socket (with jacketed tail cap)
REV/版本	A1	SIZE: A4	型号	DHG. 2BP. 312. KWLLD72Z
SHEET: 1 OF 1		PART NAME		