


1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: ϕ 5.1mm- ϕ 6.0mm




2. 电气性能

Insert Configuration/针芯配置: 2BP. 307 7Low Voltage
 Pin Size/接触件直径: ϕ 1.3mm
 Contact resistance接触电阻: \leq 5m Ω
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 1750V(AC)
 Rated working current额定工作电流: 11.0A


Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEK
 Other Shell Material/其它壳体材质 : 铜镀镍
 Insulator material/绝缘体材料 : PPS
 IP Rating/防护等级 : IP50





*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Socket front view
插座前视图



view K
K向孔位排列

DRAWN BY: 绘图: P003 CHECKED BY: 审核: Z01 APPROVED BY: 核准: P005 2024.05.28 2024.05.28 2024.05.28	 美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.														
GENERAL TOLERANCE (UNLESS SPECIFIED) \leq 10 \pm 0.1 $<$ 10 \sim \leq 20 \pm 0.15 $<$ 20 \sim \leq 50 \pm 0.3 Angle \pm 1°	<table border="1"> <tr> <td rowspan="2">  FIRST ANGLE PROJECTION </td> <td> 单位 UNIT: mm </td> <td>名称</td> <td rowspan="2"> DHA-2BP浮动插座(不带护套尾帽) DHA-2BP Floating socket (without jacketed tail cap) </td> </tr> <tr> <td> 比例 SCALE: 1:1 </td> <td>PART NAME</td> </tr> <tr> <td></td> <td> 尺寸 SIZE: A4 </td> <td>型号</td> <td>DHA. 2BP. 307. KWLLD62</td> </tr> <tr> <td> REV/版本 A1 </td> <td> SHEET: 1 OF 1 </td> <td>PART NAME</td> <td></td> </tr> </table>	 FIRST ANGLE PROJECTION	单位 UNIT: mm	名称	DHA-2BP浮动插座(不带护套尾帽) DHA-2BP Floating socket (without jacketed tail cap)	比例 SCALE: 1:1	PART NAME		尺寸 SIZE: A4	型号	DHA. 2BP. 307. KWLLD62	REV/版本 A1	SHEET: 1 OF 1	PART NAME	
 FIRST ANGLE PROJECTION	单位 UNIT: mm		名称	DHA-2BP浮动插座(不带护套尾帽) DHA-2BP Floating socket (without jacketed tail cap)											
	比例 SCALE: 1:1	PART NAME													
	尺寸 SIZE: A4	型号	DHA. 2BP. 307. KWLLD62												
REV/版本 A1	SHEET: 1 OF 1	PART NAME													