

## 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度:  $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$

Humidity(max)/最大潮湿:  $\leq 95\%$  [at 60 deg C / 140 F]

Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾: 96hr



### Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]

Shock Resistance/冲击: 100g[6ms]

Endurance (Shell)/机械寿命: 5000+

Cable/配接电缆:  $\phi 8.1\text{mm} - \phi 9.0\text{mm}$



## 2. 电气性能

Insert Configuration/针芯配置: 2BP. 303 3Low Voltage

Pin Size/接触件直径:  $\phi 1.6\text{mm}$

Contact resistance接触电阻:  $\leq 4\text{m}\Omega$

Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))

Withstand voltage/耐压: 2400V(AC)

Rated working current额定工作电流: 17.0A

### Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金


Housing Material/外壳材质: PEEK

Other Shell Material/其它壳体材质: 铜电镀


Insulator material/绝缘体材料: PEEK

IP Rating/防护等级: IP50


\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Socket front view  
插座前视图



view K  
K向孔位排列

DRAWN BY: 绘图: P003 CHECKED BY: 审核: Z01 APPROVED BY: 核准: P005	2024.05.28 2024.05.28 2024.05.28	 美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.	名称 DHA-2BP浮动式插座 (不带护套式尾帽) (without jacketed tail cap)	
			单位 UNT: mm	PART NAME
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \sim 20^{\circ} \pm 0.15$ $< 20^{\circ} \sim 50^{\circ} \pm 0.3$ Angle $\pm 1^{\circ}$		比例 SCALE: 1: 1	型号 DHA. 2BP. 303. KWKLD92	
FIRST ANGLE PROJECTION		SIZE: A4	SHEET: 3 OF 1	
REV/版本 A1		SHEET: 3 OF 1		