

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$

Humidity(max)/最大潮湿: $<95\%$ [at $60 \text{ deg C} / 140 \text{ F}$]

Shielding /屏蔽性能: $75\text{dB}(10\text{MHz}) \quad 40\text{dB}(1\text{GHz})$

Salt Spray Corrosion/盐雾: 96hr


Mechanical data/机械特性:

Vibration/振动: $15\text{g}[10\text{Hz} \sim 2000\text{Hz}]$

Shock Resistance/冲击: $100\text{g}[6\text{ms}]$

Endurance (Shell)/机械寿命: $5000+$

Cable/配接电缆: $\phi 7.1\text{mm} - \phi 8.0\text{mm}$



2. 电气性能

Insert Configuration/针芯配置: $2\text{BP}, 319, 19\text{Low Voltage}$

Pin Size/接触件直径: $\phi 0.7\text{mm}$

Contact resistance接触电阻: $\leq 12.5\text{m}\Omega$

Insulation resistance/绝缘电阻: $5000\text{M}\Omega$ (测试电压 $500\text{V}(\text{DC})$)

Withstand voltage/耐电压: $950\text{V}(\text{AC})$

Rated working current额定工作电流: 5.0A

Other Specification/其它规格:

Contact PIN/接触件: Gold plated Tin bronze/锡青铜镀金


Housing Material/外壳材质: PEEK

Other Shell Material/其它壳体材质: 铜镀镍


Insulator material/绝缘体材料: PPS

IP Rating/防护等级: IP50


*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Socket front view
插座前视图



view K
K向孔位排列

DRAWN BY: 绘图: P003 2024.05.28 CHECKED BY: 审核: Z01 2024.05.28 APPROVED BY: 核准: P005 2024.05.28		 美易连电子科技(深圳)有限公司 Meiyilian electronic technology(shenzhen)Co.,Ltd.	
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $<10^{\circ} \leq 20^{\circ} \pm 0.15$ $<20^{\circ} \leq 50^{\circ} \pm 0.3$ Angle $\pm 1^{\circ}$		单位 UNITS: mm 比例 SCALE: 1:1 名称 PART NAME DHA-2BP浮动式插座(带护套式尾帽) DHA-2BP Floating socket (with jacketed tail cup)	型号 PART NAME DHA. 2BP. 319. KWLLD82Z
FIRST ANGLE PROJECTION		REV/版本 A1	SHEET: 1 OF 1