

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度:  $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$

Humidity(max)/最大潮湿:  $<95\%$  [at  $60^{\circ}\text{C} / 140^{\circ}\text{F}$ ]

Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动:  $15\text{g}$  [10Hz~2000Hz]

Shock Resistance/冲击:  $100\text{g}$  [6ms]

Endurance (Shell)/机械寿命: 5000+

Cable/配接电缆:  $\phi 3.4\text{mm} - \phi 4.3\text{mm}$

2. 电气性能

Insert Configuration/针芯配置: 2BP, 303 3Low Voltage

Pin Size/接触件直径:  $\phi 1.6\text{mm}$

Contact resistance接触电阻:  $\leq 4\text{m}\Omega$

Insulation resistance/绝缘电阻:  $5000\text{M}\Omega$  (测试电压500V (DC))

Withstand voltage/耐电压:  $2400\text{V}$  (AC)

Rated working current额定工作电流:  $17.0\text{A}$

Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金

Housing Material/外壳材质: PEEK

Other Shell Material/其它壳体材质: 铜电镀

Insulator material/绝缘体材料: PPS

IP Rating/防护等级: IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图

A

B

C



D

A

B

C

D




DRAWN BY: 绘图: P003	2024.05.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: P005	2024.05.28

GENERAL TOLERANCE (UNLESS SPECIFIED)	
$\leq 10$	$\pm 0.1$
$< 10^{\circ} \leq 20$	$\pm 0.15$
$< 20^{\circ} \leq 50$	$\pm 0.3$
Ang Fe	$\pm 1^{\circ}$



美易连电子科技(深圳)有限公司  
Meiyilian electronic technology (shenzhen) Co., Ltd.



FIRST ANGLE PROJECTION

REV/版本	A1
--------	----

单位 UNIT: mm	名称 PART NAME	DHG-2BP浮动式插座(带护套式尾帽) DHG-2BP Floating socket (with jacketed tail cap)
比例 SCALE: 1: 1		
SIZE: A4	型号 PART NAME	DHG. 2BP. 303. KWLLD45Z
SHEET: 1 OF 1		

1

2

3

4

5

6

7

8

1

2

4

5

7

8