

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: -55℃~150℃
 Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]
 Shock Resistance/冲击: 100g[6ms]
 Endurance (Shell)/机械寿命: 5000+
 Cable/配接电缆: ϕ 5.1mm- ϕ 6.0mm

2. 电气性能



Insert Configuration/针芯配置: 2BP. 303 3Low Voltage
 Pin Size/接触件直径: ϕ 1.6mm
 Contact resistance接触电阻: \leq 4m Ω
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 2400V(AC)
 Rated working current额定工作电流: 17.0A

Other Specification/其它规格:


Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



Plug front view
插头前视图



view K
K向孔位排列

DRAWN BY:
绘图: PDD3 2021.05.28
 CHECKED BY:
审核: Z01 2024.05.28
 APPROVED BY:
核准: P005 2024.05.28



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE (UNLESS SPECIFIED)		UNIT: mm		名称	TG-2BP 直式插头 (带护套式尾罩) TG-2BP Straight Plug (with jacketed tail cap)
≤ 10	± 0.1		比例 SCALE: 1:1	PART NAME	
$10 < \leq 20$	± 0.15	SIZE: A4		型号	TGA. 2BP. 303. KWKAD62Z
$20 < \leq 50$	± 0.3	REV/版本	A1	SHEET: 1 OF 1	PART NAME
Angle	$\pm 1^\circ$				