

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C}\sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿: $\leq 95\%$ [at 60 deg C / 140 F]
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]
 Shock Resistance/冲击: 100g[6ms]
 Endurance (Shell)/机械寿命: 5000+
 Cable/配接电缆: $\phi 9.1\text{mm}\sim\phi 10.0\text{mm}$



2. 电气性能

Insert Configuration/针芯配置: 2BP. 332 32Low Voltage
 Pin Size/接触件直径: $\phi 0.5\text{mm}$
 Contact resistance接触电阻: $\leq 15\text{m}\Omega$
 Insulation resistance/绝缘电阻: 50000 Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 800V(AC)
 Rated working current 额定工作电流: 1.5A


Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PPS
 IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Plug front view
插头前视图



view K
K向孔位排列


REV/版本	DESCRIPTION/描述内容	DATE/日期	DRAWN BY/绘图

DRAWN BY: 绘图: P063	2024. 05. 28
CHECKED BY: 审核: Z01	2024. 05. 28
APPROVED BY: 核准: P005	2024. 05. 28



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE (UNLESS SPECIFIED)	
≤ 10	± 0.1
$< 10^{\circ} \sim \leq 20$	± 0.15
$< 20^{\circ} \sim \leq 50$	± 0.3
Angle	$\pm 1^{\circ}$



REV/版本	A1
--------	----

UNIT: 单位	mm	名称	TG-2BP直式插头(带护套式尾帽)
SCALE: 比例	1:1	PART NAME	TG-2BP Straight Plug (with jacketed tail cap)
SIZE: 型号	A1	型号	TGA. 2BP. 332. KWLAD102Z
SHEET: PART NAME	1 OF 1	PART NAME	