

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: -55°C~150°C

Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F]

Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾: 96hr


Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]

Shock Resistance/冲击: 100g[6ms]

Endurance (Shell)/机械寿命: 5000+

Cable/配接电缆: ϕ 5.1mm- ϕ 6.0mm



2. 电气性能

Insert Configuration/针芯配置: 2BP. 302 2Low Voltage

Pin Size/接触件直径: ϕ 2.0mm

Contact resistance接触电阻: \leq 3.5m Ω

Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))

Withstand voltage/耐电压: 2100V(AC)

Rated working current额定工作电流: 30.0A

Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金


Housing Material/外壳材质: PEEK

Other Shell Material/其它壳体材质: 铜镀镍

Insulator material/绝缘体材料: PEEK

IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



view K
K向孔位排列

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图


DRAWN BY:
绘图: PDD3 2024.05.28
CHECKED BY:
审核: Z01 2024.05.28
APPROVED BY:
核准: PDD3 2024.05.28



美易连电子科技(深圳)有限公司
Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE
(UNLESS SPECIFIED)

\leq 10 \pm 0.1
 $<10 \sim \leq$ 20 \pm 0.15
 $<20 \sim \leq$ 50 \pm 0.3
Angle \pm 1°



单位
UNIT: mm

比例
SCALE: 1:1

名称
PART NAME

型号
PART NAME

REV/版本 A1

SHEET: 1 OF 1

TG-2BP直式插头(带护套式尾帽)
TG-2BP Straight Plug
(with jacketed tail cap)

TGG. 2BP. 302. KWKAD62Z