


1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C}\sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿: $<=95\%$ [at $60\text{ deg C} / 140\text{ F}$]
 Shielding /屏蔽性能: $75\text{dB}(10\text{MHz})\ 40\text{dB}(1\text{GHz})$
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: $15\text{g}[10\text{Hz}\sim 2000\text{Hz}]$
 Shock Resistance/冲击: $100\text{g}[6\text{ms}]$
 Endurance (Shell)/机械寿命: $5000+$
 Cable/配接电缆: $\phi 10.1\text{mm}-\phi 11.0\text{mm}$



2. 电气性能


Insert Configuration/针芯配置: $3\text{BP. } 316\ 16\text{Low Voltage}$
 Pin Size/接触件直径: $\phi 0.9\text{mm}$
 Contact resistance接触电阻: $\leq 6\text{m}\Omega$
 Insulation resistance/绝缘电阻: $5000\text{M}\Omega$ (测试电压 $500\text{V}(\text{DC})$)
 Withstand voltage/耐电压: $1200\text{V}(\text{AC})$
 Rated working current额定工作电流: 8.0A

Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK

IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图

DRAWN BY: 绘图: PDD3	2024. 05. 28		美易连电子科技(深圳)有限公司 Meiyilian electronic technology(shenzhen)Co., Ltd.	
CHECKED BY: 审核: Z01	2024. 05. 28			
APPROVED BY: 核准: PDD5	2024. 05. 28			
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10\ \pm 0.1$ $< 10^{\circ} \leq 20\ \pm 0.15$ $< 20^{\circ} \leq 50\ \pm 0.3$ Angle $\pm 1^{\circ}$		FIRST ANGLE PROJECTION	单位 UNIT: mm 比例 SCALE: 1: 1 名称 PART NAME	DHG-3BP浮动式插座(不带护套式尾帽) DHG-3BP floating socket (without jacketed tail cap)
SIZE: A4 REV/版本 A1 SHEET: 1 OF 1		型号 PART NAME	DHG. 3BP. 316. KWKL12	