


# 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度:  $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$   
 Humidity(max)/最大潮湿:  $\leq 95\%$  [at 60 deg C / 140 F]  
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾: 96hr

## Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]  
 Shock Resistance/冲击: 100g[6ms]  
 Endurance (Shell)/机械寿命: 5000+  
 Cable/配接电缆:  $\phi 7.1\text{mm} - \phi 8.0\text{mm}$





# 2. 电气性能

Insert Configuration/针芯配置: 4BP. 324 24Low Voltage  
 Pin Size/接触件直径:  $\phi 0.9\text{mm}$   
 Contact resistance接触电阻:  $\leq 9\text{m}\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1200V(AC)  
 Rated working current额定工作电流: 7.0A

## Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质: PEEK  
 Other Shell Material/其它壳体材质: 铜镀镍  
 Insulator material/绝缘体材料: PEEK  
 IP Rating/防护等级: IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.




DRAWN BY: 绘图: PDD03 2024.05.28  
 CHECKED BY: 审核: Z01 2024.05.28  
 APPROVED BY: 核准: PDD05 2024.05.28

GENERAL TOLERANCE (UNLESS SPECIFIED)

$\leq 10 \pm 0.1$   
 $< 10^{\circ} \sim \leq 20 \pm 0.15$   
 $> 20^{\circ} \sim \leq 30 \pm 0.3$   
 Angle  $\pm 1^{\circ}$



美易连电子科技(深圳)有限公司  
 Meiyilian electronic technology(shenzhen)Co.,Ltd.



FIRST ANGLE PROJECTION

REV/版本 A1

单位: mm  
 比例: 1:1  
 名称: TGG-4BP  
 型号: TGG. 4BP. 324. KWKAD82

TG-4BP直式插头(不带护套式尾帽)  
 TG-4BP Straight Plug  
 (without jacketed tail cap)