

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿: $\leq 95\%$ [at $60^{\circ}\text{C} / 140^{\circ}\text{F}$]
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]
 Shock Resistance/冲击: 100g[6ms]
 Endurance (Shell)/机械寿命: 5000+
 Cable/配接电缆: $\phi 7.1\text{mm} - \phi 8.0\text{mm}$

2. 电气性能



Insert Configuration/针芯配置: 3BP. 309 9Low Voltage
 Pin Size/接触件直径: $\phi 2.0 / 1.3\text{mm}$
 Contact resistance接触电阻: $\leq 3.5\text{m}\Omega, \leq 5\text{m}\Omega$
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 1350V(AC)
 Rated working current额定工作电流: 15.0/6.0A

Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



DRAWN BY: 绘图: P003 2024.05.28 CHECKED BY: 审核: Z01 2024.05.28 APPROVED BY: 核准: P005 2024.05.28	美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.	<table border="1"> <tr> <td> 单位 UNIT: mm </td> <td> 名称 PART NAME </td> <td rowspan="2"> TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap) </td> </tr> <tr> <td> 比例 SCALE: 1: 1 </td> <td> 型号 PART NAME </td> </tr> </table>	单位 UNIT: mm	名称 PART NAME	TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)	比例 SCALE: 1: 1	型号 PART NAME						
单位 UNIT: mm			名称 PART NAME	TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)									
比例 SCALE: 1: 1	型号 PART NAME												
<table border="1"> <tr> <td> GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \leq 20 \pm 0.15$ $< 20^{\circ} \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$ </td> <td> FIRST ANGLE PROJECTION </td> <td> <table border="1"> <tr> <td> REV/版本 A1 </td> <td> SHEET: 1 OF 1 </td> </tr> </table> </td> <td> 型号 PART NAME TGG. 3BP. 309. KWKAD82 </td> </tr> </table>	GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \leq 20 \pm 0.15$ $< 20^{\circ} \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$	FIRST ANGLE PROJECTION	<table border="1"> <tr> <td> REV/版本 A1 </td> <td> SHEET: 1 OF 1 </td> </tr> </table>	REV/版本 A1	SHEET: 1 OF 1	型号 PART NAME TGG. 3BP. 309. KWKAD82	美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.	<table border="1"> <tr> <td> 单位 UNIT: mm </td> <td> 名称 PART NAME </td> <td rowspan="2"> TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap) </td> </tr> <tr> <td> 比例 SCALE: 1: 1 </td> <td> 型号 PART NAME </td> </tr> </table>	单位 UNIT: mm	名称 PART NAME	TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)	比例 SCALE: 1: 1	型号 PART NAME
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \leq 20 \pm 0.15$ $< 20^{\circ} \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$	FIRST ANGLE PROJECTION	<table border="1"> <tr> <td> REV/版本 A1 </td> <td> SHEET: 1 OF 1 </td> </tr> </table>	REV/版本 A1	SHEET: 1 OF 1	型号 PART NAME TGG. 3BP. 309. KWKAD82								
REV/版本 A1	SHEET: 1 OF 1												
单位 UNIT: mm	名称 PART NAME	TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)											
比例 SCALE: 1: 1	型号 PART NAME												
<table border="1"> <tr> <td> GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \leq 20 \pm 0.15$ $< 20^{\circ} \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$ </td> <td> FIRST ANGLE PROJECTION </td> <td> <table border="1"> <tr> <td> REV/版本 A1 </td> <td> SHEET: 1 OF 1 </td> </tr> </table> </td> <td> 型号 PART NAME TGG. 3BP. 309. KWKAD82 </td> </tr> </table>	GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \leq 20 \pm 0.15$ $< 20^{\circ} \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$	FIRST ANGLE PROJECTION	<table border="1"> <tr> <td> REV/版本 A1 </td> <td> SHEET: 1 OF 1 </td> </tr> </table>	REV/版本 A1	SHEET: 1 OF 1	型号 PART NAME TGG. 3BP. 309. KWKAD82	美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.	<table border="1"> <tr> <td> 单位 UNIT: mm </td> <td> 名称 PART NAME </td> <td rowspan="2"> TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap) </td> </tr> <tr> <td> 比例 SCALE: 1: 1 </td> <td> 型号 PART NAME </td> </tr> </table>	单位 UNIT: mm	名称 PART NAME	TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)	比例 SCALE: 1: 1	型号 PART NAME
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \leq 20 \pm 0.15$ $< 20^{\circ} \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$	FIRST ANGLE PROJECTION	<table border="1"> <tr> <td> REV/版本 A1 </td> <td> SHEET: 1 OF 1 </td> </tr> </table>	REV/版本 A1	SHEET: 1 OF 1	型号 PART NAME TGG. 3BP. 309. KWKAD82								
REV/版本 A1	SHEET: 1 OF 1												
单位 UNIT: mm	名称 PART NAME	TG-3BP直式插头(不护套套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)											
比例 SCALE: 1: 1	型号 PART NAME												