

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃  
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]  
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]  
 Shock Resistance/冲击 : 100g[6ms]  
 Endurance (Shell)/机械寿命 : 5000+  
 Cable/配接电缆:  $\phi$ 9.1mm- $\phi$ 10.0mm

2. 电气性能



Insert Configuration/针芯配置: 3BP.302 2Low Voltage  
 Pin Size/接触件直径:  $\phi$ 3.0mm  
 Contact resistance接触电阻:  $\leq$ 3m $\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V (DC))  
 Withstand voltage/耐电压: 2100V (AC)  
 Rated working current额定工作电流: 35.0A

Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质 : PEEK  
 Other Shell Material/其它壳体材质: 铜电镀  
 Insulator material/绝缘体材料: PEEK  
 IP Rating/防护等级 : IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/描述/内容	DATE/日期	DRAWN BY/绘图



DRAWN BY: 绘图: P003	2024.05.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: P005	2024.05.28
GENERAL TOLERANCE (UNLESS SPECIFIED)	
$\leq$ 10 $\pm$ 0.1	
<10° $\leq$ 20 $\pm$ 0.15	
<20° $\leq$ 50 $\pm$ 0.3	
Angle $\pm$ 1°	

		美易连电子科技(深圳)有限公司 Meiyilian electronic technology(shenzhen)Co.,Ltd.	
	比例 SCALE: 1:1	PART NAME	
SIZE: A4	型号 SHEET: 1 OF 1	PART NAME	TGG.3BP.302.KWKAD102Z
REV/版本	A1		

1

2

<https://www.myconnector.com/>

4

5

<https://www.myconnector.com/>

7

8