

# 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度:  $-55^{\circ}\text{C}\sim 150^{\circ}\text{C}$   
 Humidity(max)/最大潮湿:  $\leq 95\%$  [at 60 deg C / 140 F]  
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾: 96hr

## Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]  
 Shock Resistance/冲击: 100g[6ms]  
 Endurance (Shell)/机械寿命: 5000+  
 Cable/配接电缆:  $\phi 9.1\text{mm}-\phi 10.0\text{mm}$



## 2. 电气性能

Insert Configuration/针芯配置: 3BP.307 7Low Voltage  
 Pin Size/接触件直径:  $\phi 1.6\text{mm}$   
 Contact resistance接触电阻:  $\leq 4\text{m}\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1700V(AC)  
 Rated working current额定工作电流: 15.0A

## Other Specification/其它规格:



Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质: PEEK  
 Other Shell Material/其它壳体材质: 铜镀镍  
 Insulator material/绝缘体材料: PEEK  
 IP Rating/防护等级: IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Socket front view  
插座前视图

view K  
K向孔位排列

DRAWN BY: 绘图: P003		2024.05.28			<b>美易连电子科技(深圳)有限公司</b> Meiyilian electronic technology (shenzhen) Co., Ltd.		
CHECKED BY: 审核: Z01		2024.05.28					
APPROVED BY: 批准: P005		2024.05.28					
GENERAL TOLERANCE (UNLESS SPECIFIED)				 FIRST ANGLE PROJECTION	单位 UNIT: mm	名称	DHA-3BP浮动式插座(不带护套式尾帽) DHA-3BP Floating socket (without jacketed tail cap)
$\leq 10 \pm 0.1$					比例 SCALE: 1:1	PART NAME	
$< 10^{\circ} \leq 20^{\circ} \pm 0.15$					SIZE: A4	型号 PART NAME	
$> 20^{\circ} \leq 50^{\circ} \pm 0.3$					REV/版本 A1		
Angle $\pm 1^{\circ}$							