

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: $\phi 10.9\text{mm}-\phi 11.8\text{mm}$

2. 电气性能



Insert Configuration/针芯配置:3BP.302 2Low Voltage
 Pin Size/接触件直径: $\phi 3.0\text{mm}$
 Contact resistance接触电阻: $\leq 3\text{m}\Omega$
 Insulation resistance/绝缘电阻:5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压:2100V(AC)
 Rated working current额定工作电流:35.0A

Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PPS
 IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/更改内容	DATE/日期	DRAWN BY/绘图




DRAWN BY: 绘图: P003	2024. 05. 28
CHECKED BY: 审核: Z01	2024. 05. 28
APPROVED BY: 核准: P005	2024. 05. 28



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE (UNLESS SPECIFIED)	UNT: mm	名称	TG-3BP 直式插头 (带护套式尾帽)
$\leq 10 \pm 0.1$	比例	PART NAME	TG-3BP Straight Plug (with jacketed tail cap)
$< 10^\circ \leq 20 \pm 0.15$	SCALE: 1: 1	型号	TGG. 3BP. 302. KWLAD120Z
$< 20^\circ \leq 50 \pm 0.3$	SIZE: A1	PART NAME	
AngLe $\pm 1^\circ$	REV/版本	A1	SHEET: 1 OF 1



FIRST ANGLE PROJECTION

1

2

<https://www.mylconnector.com/>

4

5

<https://www.mylconnector.com/>

7

8