REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图

1.Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃～150℃
Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
Salt Spray Corrosion/盐 雾 : 96hr

Mechanical data/机械特性:
Vibration/振 动 : 15g[10Hz～2000Hz]
Shock Resistance/冲 击 : 100g[6ms]
Endurance (Shell)/机械寿命 : 5000+
Cable/配接电缆:Φ7.1mm-Φ8.0mm





2.电气性能

Insert Configuration/针芯配置:3BP.316 16Low Voltage
Pin Size/接触件直径:Φ0.9mm
Contact resistance接触电阻:≤6mΩ
Insulation resistance/绝缘电阻:5000MΩ(测试电压500V(DC))
Withstand voltage/耐电压:1200V(AC)
Rated working current额定工作电流:8.0A

Other Specification/其它规格:
Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
Housing Material/外壳材质 : PEEK
Other Shell Material/其它壳体材质: 铜镀镍
Insulator material/绝缘体材料: PEEK
IP Rating/防护等级 : IP50
*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Plug front view
插头前视图

view K
K向孔位排列

DRAWN BY: 绘图:PD03 2024.05.28 CHECKED BY: 审核:ZO1 2024.05.28 APPROVED BY: 核准:PD05 2024.05.28	MEIYILIAN 美易连电子科技（深圳）有限公司 Meiyilian electronic technology(shenzhen)Co.,Ltd.		
GENERAL TOLERANCE (UNLESS SPECIFIED) ≤10 ±0.1 10~≤20 ±0.15 20~≤50 ±0.3 Angle ±1°	FIRST ANGLE PROJECTION REV/版本 A1	单位 UNIT: mm 比例 SCALE: 1:1 SIZE: A4 SHEET:1 OF 1	名称 PART NAME: TG-3BP直式插头（不带护套式尾帽）TG-3BP Straight Plug (without jacketed tail cap) 型号 PART NAME: TGA.3BP.316.KWKAD82Z

https://www.myiconnector.com/