

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃

Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]

Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]

Shock Resistance/冲击 : 100g[6ms]

Endurance (Shell)/机械寿命 : 5000+

Cable/配接电缆: $\phi 4.1\text{mm}-\phi 5.0\text{mm}$

2. 电气性能

Insert Configuration/针芯配置: 3BP. 304 4Low Voltage

Pin Size/接触件直径: $\phi 2.0\text{mm}$

Contact resistance接触电阻: $\leq 3.5\text{m}\Omega$

Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))

Withstand voltage/耐电压: 1450V(AC)

Rated working current额定工作电流: 19.0A

Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金

Housing Material/外壳材质 : PEEK



Other Shell Material/其它壳体材质: 铜镀镍

Insulator material/绝缘体材料: PEEK

IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图




view K
K向孔位排列

DRAWN BY: 绘图: P003	2024.03.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: P005	2024.05.28



美易连电子科技(深圳)有限公司
Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE (UNLESS SPECIFIED)	UNIT: mm	名称	DHG-3BP浮动式插座(不带护套式尾帽) DHG-3BP Floating socket (without jacketed tail cap)
≤ 10 ± 0.1	比例 SCALE: 1: 1	PART NAME	
$< 10^{\circ} \sim \leq 20$ ± 0.15	SIZE: A4	型号	DHG. 3BP. 304. KWKLD52
$< 20^{\circ} \sim \leq 50$ ± 0.3	REV/版本	A1	SHEET: 1 OF 1
Angle $\pm 1^{\circ}$			



FIRST ANGLE PROJECTION

REV/版本

<https://www.myconnector.com/>

<https://www.myconnector.com/>