

1. Product main performance / 产品主要性能指标:

Operating Temperature / 工作温度: $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
 Humidity(max) / 最大潮湿: $< 95\%$ [at 60 deg C / 140 F]
 Shielding / 屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion / 盐雾: 96hr

Mechanical data / 机械特性:

Vibration / 振动: 15g[10Hz~2000Hz]
 Shock Resistance / 冲击: 100g[6ms]
 Endurance (Shell) / 机械寿命: 5000+
 Cable / 配接电缆: $\phi 14.1\text{mm} - \phi 15.0\text{mm}$

2. 电气性能




Insert Configuration / 针芯配置: 4BP, 348 48Low Voltage
 Pin Size / 接触件直径: $\phi 0.7\text{mm}$
 Contact resistance / 接触电阻: $\leq 12.5\text{m}\Omega$
 Insulation resistance / 绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage / 耐电压: 700V(AC)
 Rated working current / 额定工作电流: 1.5A

Other Specification / 其它规格:

Contact PIN / 接触体: Gold plated Tin bronze / 锡青铜镀金
 Housing Material / 外壳材质: PEEK
 Other Shell Material / 其它壳体材质: 铜镀镍
 Insulator material / 绝缘体材料: PPS
 IP Rating / 防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT / 所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图




DRAWN BY: 绘图: P003 2024.05.28
 CHECKED BY: 审核: Z01 2024.05.28
 APPROVED BY: 核准: P005 2024.05.28

GENERAL TOLERANCE
 (UNLESS SPECIFIED)
 $\leq 10 \pm 0.1$
 $< 10^{\circ} \leq 20 \pm 0.15$
 $< 20^{\circ} \leq 30 \pm 0.3$
 Angle $\pm 1^{\circ}$



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology (shenzhen) Co., Ltd.



FIRST ANGLE PROJECTION

单位
 UNIT: mm
 比例
 SCALE: 1:1

名称
 PART NAME

型号
 PART NAME

REV/版本
 SHEET: 1 OF 1

TG-4BP直式插头(不带护套式尾帽)
 TG-4BP Straight Plug
 (without jacketed tail cap)

TGG_4BP_348_KWLAD152