

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃

Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]

Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]

Shock Resistance/冲击 : 100g[6ms]

Endurance (Shell)/机械寿命 : 5000+

Cable/配接电缆: $\phi 10.1\text{mm}-\phi 11.0\text{mm}$

2. 电气性能

Insert Configuration/针芯配置:3BP.308 8Low Voltage

Pin Size/接触件直径: $\phi 1.3\text{mm}$

Contact resistance接触电阻: $\leq 5\text{m}\Omega$

Insulation resistance/绝缘电阻:5000M Ω (测试电压500V(DC))

Withstand voltage/耐电压:1650V(AC)

Rated working current额定工作电流:13.0A

Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金

Housing Material/外壳材质 : PEEK



Other Shell Material/其它壳体材质: 铜镀镍

Insulator material/绝缘体材料: PEEK

IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



DRAWN BY: 绘图: P003	2024.05.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: P003	2024.05.28



美易连电子科技(深圳)有限公司
Meiyilian electronic technology(shenzhen)Co.,Ltd.

<p>GENERAL TOLERANCE (UNLESS SPECIFIED)</p> <p>$\leq 10 \pm 0.1$</p> <p>$< 10^\circ \leq 20 \pm 0.15$</p> <p>$< 20^\circ \leq 50 \pm 0.3$</p> <p>Angle $\pm 1^\circ$</p>	<p>FIRST ANGLE PROJECTION</p>	<p>单位 UNIT: mm</p>	<p>名称 PART NAME</p>	<p>TG-3BP直式插头(带护套式尾帽) TG-3BP Straight Plug (with jacketed tail cap)</p>
		<p>比例 SCALE: 1: 1</p>	<p>型号 PART NAME</p>	
<p>REV/版本</p>	<p>A1</p>	<p>SHEET: 1 OF 1</p>	<p>型号 PART NAME</p>	<p>TGG.3BP.308.KWKAD112Z</p>