

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: $-55^{\circ}\text{C}\sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿: $<=95\%$ [at 60 deg C / 140 F]
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]
 Shock Resistance/冲击: 100g[6ms]
 Endurance (Shell)/机械寿命: 5000+
 Cable/配接电缆: $\phi 8.1\text{mm}-\phi 9.0\text{mm}$



2. 电气性能

Insert Configuration/针芯配置: 3BP. 306 6Low Voltage
 Pin Size/接触件直径: $\phi 1.6\text{mm}$
 Contact resistance接触电阻: $\leq 4\text{m}\Omega$
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐压: 1600V(AC)
 Rated working current额定工作电流: 17.0A


Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级: IP50



*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Socket front view
插座前视图



view K
K向孔位排列

DRAWN BY: 绘图: P003		2024. 05. 28			美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co. .Ltd.	
CHECKED BY: 审核: Z01		2024. 05. 28				
APPROVED BY: 核准: P003		2024. 05. 28				
GENERAL TOLERANCE (UNLESS SPECIFIED)					名称 PART NAME	DHA-3BP浮动式插座 (不带护套式尾帽) DHA-3BP floating socket (without jacketed tail cap)
$\leq 10 \pm 0.1$ $< 10^{\circ} \sim \leq 20 \pm 0.15$ $< 20^{\circ} \sim \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$						
REV/版本		A1		单位 UNIT: mm	型号 PART NAME	DHA. 3BP. 306. KWKL92
				比例 SCALE: 1: 1		
				SIZE: A4		
				第一角投影 FIRST ANGLE PROJECTION		
				SHEET: 1 OF 1		