

# 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: -55°C~150°C  
 Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F]  
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾: 96hr

## Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]  
 Shock Resistance/冲击: 100g[6ms]  
 Endurance (Shell)/机械寿命: 5000+  
 Cable/配接电缆:  $\phi$ 5.1mm- $\phi$ 6.0mm

## 2. 电气性能



Insert Configuration/针芯配置: 3BP. 308 8Low Voltage  
 Pin Size/接触件直径:  $\phi$ 1.3mm  
 Contact resistance接触电阻:  $\leq$ 5m $\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1650V(AC)  
 Rated working current额定工作电流: 13.0A



## Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质: PEEK  
 Other Shell Material/其它壳体材质: 铜镀镍  
 Insulator material/绝缘体材料: PEEK  
 IP Rating/防护等级: IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



DRAWN BY: 绘图: P003 审核: Z01 APPROVED BY: 核准: P005 2024.05.28 2024.05.28 2024.05.28	 美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.	单位: mm 名称: TG-3BP 直式插头 (带护套式尾帽) 比例: 1:1 名称: TG-3BP Straight Plug 比例: 1:1 名称: (with jacketed tail cap) 型号: TGG. 3BP. 308. KWKAD62Z 型号: TGG. 3BP. 308. KWKAD62Z	
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10$ $\pm 0.1$ $< 10 \sim \leq 20$ $\pm 0.15$ $< 20 \sim \leq 50$ $\pm 0.3$ Angle $\pm 1^\circ$	 FIRST ANGLE PROJECTION	尺寸: A4 名称: TGG. 3BP. 308. KWKAD62Z 型号: TGG. 3BP. 308. KWKAD62Z	
REV/版本	A1	SHEET: 1 OF 1	PART NAME