

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: -55°C~150°C
 Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾: 96hr

Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]
 Shock Resistance/冲击: 100g[6ms]
 Endurance (Shell)/机械寿命: 5000+
 Cable/配接电缆: $\phi 6.1\text{mm}-\phi 7.0\text{mm}$

2. 电气性能




Insert Configuration/针芯配置: 4BP. 304 4Low Voltage
 Pin Size/接触件直径: $\phi 3.0\text{mm}$
 Contact resistance接触电阻: $\leq 3\text{m}\Omega$
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 2100V(AC)
 Rated working current额定工作电流: 30.0A

Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PPS
 IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



DRAWN BY: 绘图: P003	2024.05.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: P005	2024.05.28

		美易连电子科技(深圳)有限公司 Meiyilian electronic technology(shenzhen)Co.,Ltd.	
		单位 UNIT: mm 名称 PART NAME TG-4BP 直式插头 (不带护套式尾帽) TG-4BP Straight Plug (without jacketed tail cap)	比例 SCALE: 1:1 型号 TGG.4BP.304.KWLAD72
名称 PART NAME TG-4BP 直式插头 (不带护套式尾帽) (without jacketed tail cap)	比例 SCALE: 1:1 型号 TGG.4BP.304.KWLAD72	单位 UNIT: mm 名称 PART NAME TG-4BP 直式插头 (不带护套式尾帽) (without jacketed tail cap)	比例 SCALE: 1:1 型号 TGG.4BP.304.KWLAD72
名称 PART NAME TG-4BP 直式插头 (不带护套式尾帽) (without jacketed tail cap)	比例 SCALE: 1:1 型号 TGG.4BP.304.KWLAD72	单位 UNIT: mm 名称 PART NAME TG-4BP 直式插头 (不带护套式尾帽) (without jacketed tail cap)	比例 SCALE: 1:1 型号 TGG.4BP.304.KWLAD72
名称 PART NAME TG-4BP 直式插头 (不带护套式尾帽) (without jacketed tail cap)	比例 SCALE: 1:1 型号 TGG.4BP.304.KWLAD72	单位 UNIT: mm 名称 PART NAME TG-4BP 直式插头 (不带护套式尾帽) (without jacketed tail cap)	比例 SCALE: 1:1 型号 TGG.4BP.304.KWLAD72

GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10 \sim 20 \pm 0.15$ $< 20 \sim 50 \pm 0.3$ Angle $\pm 1^\circ$	
FIRST ANGLE PROJECTION	REV/版本 A1 SHEET: 1 OF 1