

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: ϕ 14.1mm- ϕ 15.0mm

2. 电气性能


Insert Configuration/针芯配置: 4BP. 306 6Low Voltage
 Pin Size/接触件直径: ϕ 2.0mm
 Contact resistance接触电阻: \leq 3.5m Ω
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 2000V(AC)
 Rated working current额定工作电流: 24.0A

Other Specification/其它规格:


Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/设计



定位销: 1/Key




DRAWN BY:
绘图: PDD3 2024.05.28
 CHECKED BY:
审核: ZOI 2024.05.28
 APPROVED BY:
核准: PDD5 2024.05.28



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE
(UNLESS SPECIFIED)
 ≤ 10 ± 0.1
 $< 10 \sim \leq 20$ ± 0.15
 $< 20 \sim \leq 50$ ± 0.3
 Angle $\pm 1^\circ$



FIRST ANGLE PROJECTION

单位
UNT: mm
 比例
SCALE: 1: 1

名称
PART NAME

TG-4BP 直式插头 (护套套式尾帽)
 TG-4BP Straight Plug
 (with jacketed tail cap)

型号
PART NAME

TGG. 4BP. 306. KWKAD152Z

REV/版本 A1

SHEET: 1 OF 1