

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿 : $\leq 95\%$ [at $60 \text{ deg C} / 140 \text{ F}$]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: $\phi 5.1\text{mm} - \phi 6.0\text{mm}$

2. 电气性能



Insert Configuration/针芯配置: 3BP. 309 9Low Voltage
 Pin Size/接触件直径: $\phi 2.0/1.3\text{mm}$
 Contact resistance接触电阻: $\leq 3.5\text{m}\Omega, 5\text{m}\Omega$
 Insulation resistance/绝缘电阻: $5000\text{M}\Omega$ (测试电压500V(DC))
 Withstand voltage/耐电压: 1350V(AC)
 Rated working current额定工作电流: 15.0/6.0A

Other Specification/其它规格:


Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质: PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级: IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.


| REV/版本 | DESCRIPTION/变更内容 | DATE/日期 | DRAWN BY/绘制 |
|--------|------------------|---------|-------------|
| | | | |



Socket front view
插座前视图



view K
K向孔位排列

| | | | | |
|---|------------|---|------------------------------|---|
| DRAWN BY: 绘图: P003 | 2024.05.28 |  美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd. | 名称 | DHA-3BP浮动式插座 (不带护套式尾帽) |
| CHECKED BY: 审核: Z01 | 2024.05.28 | | PART NAME | DHA-3BP Floating socket (without jacketed tail cap) |
| APPROVED BY: 核准: P005 | 2024.05.28 | | 型号 | DHA. 3BP. 309. KWKLD62 |
| GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \sim \leq 20 \pm 0.15$ $< 20^{\circ} \sim \leq 50 \pm 0.3$ Angle $\pm 1^{\circ}$ | | 单位 UNIT: mm 比例 SCALE: 1:1 名称 PART NAME 型号 PART NAME 比例 SCALE: 1:1 名称 PART NAME | 名称 PART NAME 型号 PART NAME | 名称 PART NAME 型号 PART NAME |
| FIRST ANGLE PROJECTION | | SIZE: A4 REV/版本 A1 SHEET: 1 OF 1 | 名称 PART NAME 型号 PART NAME | 名称 PART NAME 型号 PART NAME |