

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55°C~150°C
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: ϕ 13.1mm- ϕ 14.0mm

2. 电气性能



Insert Configuration/针芯配置: 4BP. 348 48Low Voltage
 Pin Size/接触件直径: ϕ 0.7mm
 Contact resistance接触电阻: \leq 12.5m Ω
 Insulation resistance/绝缘电阻: 5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压: 700V(AC)
 Rated working current额定工作电流: 1.5A

Other Specification/其它规格:


Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PPS
 IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘制



Plug front view
插头前视图



view K
K向孔位排列

DRAWN BY: 绘图: PDD3	2024.05.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: PDD5	2024.05.28



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology(shenzhen)Co.,Ltd.

GENERAL TOLERANCE (UNLESS SPECIFIED)	≤ 10 ± 0.1 $< 10^\circ \leq 20$ ± 0.15 $< 20^\circ \leq 50$ ± 0.3 Angle $\pm 1^\circ$
---	---



FIRST ANGLE PROJECTION

REV/版本	A1	SHEET: 1 OF 1
--------	----	---------------

单位 UNIT: mm	名称 PART NAME
比例 SCALE: 1: 1	型号 PART NAME
SIZE: A4	

TG-4BP直式插头(带护套式尾帽)
 TG-4BP Straight Plug
 (with jacketed tail cap)

TGG. 4BP. 348. KWLAD142Z