

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃  
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]  
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]  
 Shock Resistance/冲击 : 100g[6ms]  
 Endurance (Shell)/机械寿命 : 5000+  
 Cable/配接电缆:  $\phi 7.1\text{mm}-\phi 8.0\text{mm}$

2. 电气性能



Insert Configuration/针芯配置: 4BP. 316 16Low Voltage  
 Pin Size/接触件直径:  $\phi 0.9\text{mm}$   
 Contact resistance接触电阻:  $\leq 4\text{m}\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1350V(AC)  
 Rated working current额定工作电流: 10.0A





Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质 : PEEK  
 Other Shell Material/其它壳体材质: 铜镀镍  
 Insulator material/绝缘体材料: PPS  
 IP Rating/防护等级 : IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘制



DRAWN BY: 绘图: P003      2024.05.28 CHECKED BY: 审核: Z01      2024.05.28 APPROVED BY: 核准: P005      2024.05.28	 美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.							
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10 \sim \leq 20 \pm 0.15$ $< 20 \sim \leq 50 \pm 0.3$ Angle $\pm 1^\circ$	<table border="1"> <tr> <td rowspan="2">                       FIRST ANGLE PROJECTION                 </td> <td>                     单位                      UNIT: mm                 </td> <td>                     名称                      PART NAME                 </td> <td>                     TG-4BP直式插头(护套套式尾帽)                      TG-4BP Straight Plug                      (with jacketed tail cap)                 </td> </tr> <tr> <td>                     比例                      SCALE: 1: 1                 </td> <td>                     型号                      PART NAME                 </td> <td>                     TGG. 4BP. 316. KWLAD82Z                 </td> </tr> </table>	 FIRST ANGLE PROJECTION	单位 UNIT: mm	名称 PART NAME	TG-4BP直式插头(护套套式尾帽) TG-4BP Straight Plug (with jacketed tail cap)	比例 SCALE: 1: 1	型号 PART NAME	TGG. 4BP. 316. KWLAD82Z
 FIRST ANGLE PROJECTION	单位 UNIT: mm		名称 PART NAME	TG-4BP直式插头(护套套式尾帽) TG-4BP Straight Plug (with jacketed tail cap)				
	比例 SCALE: 1: 1	型号 PART NAME	TGG. 4BP. 316. KWLAD82Z					
REV/版本      A1      SHEET: 1 OF 1	日期: 2024.05.28							