

## 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃  
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]  
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾 : 96hr

### Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]  
 Shock Resistance/冲击 : 100g[6ms]  
 Endurance (Shell)/机械寿命 : 5000+  
 Cable/配接电缆:  $\phi 10.9\text{mm}-\phi 11.8\text{mm}$



## 2. 电气性能

Insert Configuration/针芯配置: 3BP. 306 6Low Voltage  
 Pin Size/接触件直径:  $\phi 1.6\text{mm}$   
 Contact resistance接触电阻:  $\leq 4\text{m}\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1600V(AC)  
 Rated working current额定工作电流: 17.0A

### Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质 : PEEK  
 Other Shell Material/其它壳体材质 : 铜镀镍  
 Insulator material/绝缘体材料: PPS  
 IP Rating/防护等级 : IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Plug front view  
插头前视图



view K  
K向孔位排列

| REV/版本 | DESCRIPTION/变更内容 | DATE/日期 | DRAWN BY/绘图 |
|--------|------------------|---------|-------------|
|        |                  |         |             |

|                          |            |
|--------------------------|------------|
| DRAWN BY:<br>绘图: P003    | 2024.05.28 |
| CHECKED BY:<br>审核: Z01   | 2024.05.28 |
| APPROVED BY:<br>核准: P005 | 2024.05.28 |



美易连电子科技(深圳)有限公司  
 Meiyilian electronic technology (shenzhen) Co., Ltd.

|   |                  |                 |  |
|---|------------------|-----------------|--|
| GENERAL TOLERANCE<br>(UNLESS SPECIFIED) | UNIT: mm         | 名称<br>PART NAME | TG-3BP直式插头(带护套式尾帽)<br>TG-3BP Straight Plug<br>(with jacketed tail cap) |
| $\leq 10 \pm 0.1$                       | 比例<br>SCALE: 1:1 | 型号<br>PART NAME | TGA. 3BP. 306. KWLAD120Z   |
| $< 10 \sim \leq 20 \pm 0.15$            | SIZE: A4         |                 |  |
| $< 20 \sim \leq 50 \pm 0.3$             |                  |                 |  |
| Angle $\pm 1^\circ$                     |                  |                 |  |



FIRST ANGLE PROJECTION

|        |    |               |
|--------|----|---------------|
| REV/版本 | A1 | SHEET: 1 OF 1 |
|--------|----|---------------|