

# 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃  
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]  
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾 : 96hr

## Mechanical data/机械特性:

Vibration/振 动 : 15g[10Hz~2000Hz]  
 Shock Resistance/冲 击 : 100g[6ms]  
 Endurance (Shell)/机械寿命 : 5000+  
 Cable/配接电缆:  $\phi 4.1\text{mm}-\phi 5.0\text{mm}$



## 2. 电气性能

Insert Configuration/针芯配置: 3BP. 324 24Low Voltage  
 Pin Size/接触件直径:  $\phi 0.7\text{mm}$   
 Contact resistance接触电阻:  $\leq 4.5\text{m}\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 950V(AC)  
 Rated working current额定工作电流: 4.0A


## Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质 : PEEK  
 Other Shell Material/其它壳体材质: 铜镀镍  
 Insulator material/绝缘体材料: PPS  
 IP Rating/防护等级 : IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Socket front view  
插座前视图



view K  
K向孔位排列

| REV/版本 | DESCRIPTION/变更内容 | DATE/日期 | DRAWN BY/绘图 |
|--------|------------------|---------|-------------|
|        |                  |         |             |

|  |            |                        |  |   |
|--|------------|------------------------|--|---|
| DRAWN BY:<br>绘图: P003  | 2024.05.28 |                        | 美易连电子科技(深圳)有限公司<br>Meiyilian electronic technology(shenzhen)Co.,Ltd. |   |
| CHECKED BY:<br>审核: Z01   | 2024.05.28 |                        |  |   |
| APPROVED BY:<br>核准: P005   | 2024.05.28 |                        |  |   |
| GENERAL TOLERANCE<br>(UNLESS SPECIFIED)<br>$\leq 10 \pm 0.1$<br>$< 10^\circ \leq 20 \pm 0.15$<br>$< 20^\circ \leq 50 \pm 0.3$<br>Angle $\pm 1^\circ$ |            | FIRST ANGLE PROJECTION | 单位: mm<br>名称: PART NAME<br>比例: SCALE: 1:1<br>尺寸: A4<br>型号: PART NAME | DHA-3BP浮动式插座(带护套式尾帽)<br>DHA-3BP Floating socket<br>(with jacketed tail cap) |
| REV/版本   | A1         | SHEET: 1 OF 1          | 型号: DHA. 3BP. 324. KWLLD52Z  |   |