

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: -55℃~150℃

Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F]

Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾: 96hr


Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]

Shock Resistance/冲击: 100g[6ms]

Endurance (Shell)/机械寿命: 5000+

Cable/配接电缆:  $\phi$ 11.1mm- $\phi$ 12.0mm



2. 电气性能

Insert Configuration/针芯配置: 4BP. 330 30Low Voltage

Pin Size/接触件直径:  $\phi$ 0.9mm

Contact resistance接触电阻:  $\leq$ 9m $\Omega$

Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))

Withstand voltage/耐电压: 950V(AC)

Rated working current额定工作电流: 5.0A

Other Specification/其它规格:

Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金


Housing Material/外壳材质: PEEK

Other Shell Material/其它壳体材质: 铜镀镍


Insulator material/绝缘体材料: PEEK

IP Rating/防护等级: IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Plug front view  
插头前视图



view K  
K向孔位排列


DRAWN BY:  
绘图: P003 2024.05.28  
CHECKED BY:  
审核: Z01 2024.05.28  
APPROVED BY:  
核准: P005 2024.05.28



美易连电子科技(深圳)有限公司  
Meiyilian electronic technology(shenzhen)Co.,Ltd.

GENERAL TOLERANCE  
(UNLESS SPECIFIED)

$\leq$ 10  $\pm$ 0.1  
 $<$ 10 $^{\circ}$  $\leq$ 20  $\pm$ 0.15  
 $<$ 20 $^{\circ}$  $\leq$ 50  $\pm$ 0.3  
Angle  $\pm$ 1 $^{\circ}$



FIRST ANGLE PROJECTION

单位

UNT: mm

比例

SCALE: 1:1

SIZE: A4

REV/版本

A1

SHEET: 1 OF 1

名称

PART NAME

型号

PART NAME

TG-4BP直式插头(带护套式尾帽)  
TG-4BP Straight Plug  
(with jacketed tail cap)

TGG. 4BP. 330. KWKAD122Z