

## 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃  
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]  
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾 : 96hr

### Mechanical data/机械特性:

Vibration/振 动 : 15g[10Hz~2000Hz]  
 Shock Resistance/冲 击 : 100g[6ms]  
 Endurance (Shell)/机械寿命 : 5000+  
 Cable/配接电缆:  $\phi 10.1\text{mm}-\phi 11.0\text{mm}$

## 2. 电气性能



Insert Configuration/针芯配置: 3BP.305 5Low Voltage  
 Pin Size/接触件直径:  $\phi 1.6\text{mm}$   
 Contact resistance接触电阻:  $\leq 4\text{m}\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1900V(AC)  
 Rated working current额定工作电流: 19.0A

### Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质 : PEEK  
 Other Shell Material/其它壳体材质 : 铜镀镍  
 Insulator material/绝缘体材料 : PPS  
 IP Rating/防护等级 : IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



view K  
K向孔位排列

DRAWN BY: 绘图: P003	2024.05.28
CHECKED BY: 审核: Z01	2024.05.28
APPROVED BY: 核准: P005	2024.05.28



美易连电子科技(深圳)有限公司  
 Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE (UNLESS SPECIFIED)	公差 UNIT: mm	名称 PART NAME	DHG-3BP浮动式插座(带护套式尾帽) DHG-3BP Floating socket (with jacketed tail cap)
$\leq 10$ $\pm 0.1$	比例 SCALE: 1:1	型号 PART NAME	
$< 10^\circ \leq 20$ $\pm 0.15$	FIRST ANGLE PROJECTION	SIZE: A4	DHG. 3BP. 305. KWLLD112Z
$< 20^\circ \leq 50$ $\pm 0.3$	REV/版本	A1 SHEET: 1 OF 1	
Angle $\pm 1'$			



FIRST ANGLE PROJECTION

REV/版本

https://www.myconnector.com/

https://www.myconnector.com/