

I. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
 Humidity(max)/最大潮湿 : $\leq 95\%$ [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: $\phi 9.1\text{mm} - \phi 10.0\text{mm}$

2. 电气性能



Insert Configuration/针芯配置: 3BP. 316 16Low Voltage
 Pin Size/接触件直径: $\phi 0.9\text{mm}$
 Contact resistance接触电阻: $\leq 6\text{m}\Omega$
 Insulation resistance/绝缘电阻: 50000 Ω (测试电压500V (DC))
 Withstand voltage/耐电压: 1200V (AC)
 Rated working current额定工作电流: 8.0A

Other Specification/其它规格:


Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEEK
 Other Shell Material/其它壳体材质 : 铜镀镍
 Insulator material/绝缘体材料: PPS
 IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘制



Plug front view
插头前视图



view K
K向孔位排列

DRAWN BY: 绘图: P003 2024.05.28 CHECKED BY: 审核: Z01 2024.05.28 APPROVED BY: 核准: P005 2024.05.28	美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.			
GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10 \pm 0.1$ $< 10^{\circ} \sim 20^{\circ} \pm 0.15$ $< 20^{\circ} \sim 50^{\circ} \pm 0.3$ Angle $\pm 1^{\circ}$	<table border="1"> <tr> <td rowspan="2"> FIRST ANGLE PROJECTION </td> <td> 单位 UNT: mm 比例 SCALE: 1:1 名称 PART NAME TGA-3BP直式插头(不带护套式尾帽) TG-3BP Straight Plug (without jacketed tail cap) </td> </tr> <tr> <td> 型号 PART NAME TGA. 3BP. 316. KWLAD102Z </td> </tr> </table>	FIRST ANGLE PROJECTION	单位 UNT: mm 比例 SCALE: 1:1 名称 PART NAME TGA-3BP直式插头(不带护套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)	型号 PART NAME TGA. 3BP. 316. KWLAD102Z
FIRST ANGLE PROJECTION	单位 UNT: mm 比例 SCALE: 1:1 名称 PART NAME TGA-3BP直式插头(不带护套式尾帽) TG-3BP Straight Plug (without jacketed tail cap)			
	型号 PART NAME TGA. 3BP. 316. KWLAD102Z			
REV/版本 A1	SHEET: 1 OF 1			