

## 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55℃~150℃

Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]

Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)

Salt Spray Corrosion/盐雾 : 96hr

### Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]

Shock Resistance/冲击 : 100g[6ms]

Endurance (Shell)/机械寿命 : 5000+

Cable/配接电缆:  $\phi 9.1\text{mm}-\phi 10.0\text{mm}$

## 2. 电气性能

Insert Configuration/针芯配置: 3BP. 316 16Low Voltage

Pin Size/接触件直径:  $\phi 0.9\text{mm}$

Contact resistance接触电阻:  $\leq 6\text{m}\Omega$

Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))

Withstand voltage/耐电压: 1200V(AC)

Rated working current额定工作电流: 8.0A

### Other Specification/其它规格:

Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金



Housing Material/外壳材质 : PEEK

Other Shell Material/其它壳体材质 : 铜电镀


Insulator material/绝缘体材料: PPS

IP Rating/防护等级 : IP50

\*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.



Socket front view  
插座前视图



view K  
K向孔位排列

DRAWN BY:  
绘图: PDD3 2024.03.28  
CHECKED BY:  
审核: Z01 2024.03.28  
APPROVED BY:  
核准: PDD5 2024.03.28



美易连电子科技(深圳)有限公司

Meiyilian electronic technology (shenzhen) Co., Ltd.


GENERAL TOLERANCE  
(UNLESS SPECIFIED)

$\leq 10 \pm 0.1$

$< 10^\circ \sim \leq 20 \pm 0.15$

$< 20^\circ \sim \leq 50 \pm 0.3$

Angle  $\pm 1^\circ$



FIRST ANGLE PROJECTION

单位  
UNIT: mm

名称  
PART NAME

比例  
SCALE: 1:1

型号  
PART NAME

尺寸  
SIZE: A4

REV/版本  
A1

SHEET: 1 OF 1

DHA-3BP浮动式插座(带护套式尾帽)  
DHA-3BP Floating socket  
(with jacketed tail cap)

DHA. 3BP. 316. KWLLD102Z