

1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度 : -55°C~150°C
 Humidity(max)/最大潮湿 : <=95% [at 60 deg C / 140 F]
 Shielding /屏蔽性能 : 75dB(10MHz) 40dB(1GHz)
 Salt Spray Corrosion/盐雾 : 96hr

Mechanical data/机械特性:

Vibration/振动 : 15g[10Hz~2000Hz]
 Shock Resistance/冲击 : 100g[6ms]
 Endurance (Shell)/机械寿命 : 5000+
 Cable/配接电缆: ϕ 7.1mm- ϕ 8.0mm

2. 电气性能



Insert Configuration/针芯配置:3BP.312 12Low Voltage
 Pin Size/接触件直径: ϕ 0.9mm
 Contact resistance接触电阻: \leq 6m Ω
 Insulation resistance/绝缘电阻:5000M Ω (测试电压500V(DC))
 Withstand voltage/耐电压:1450V(AC)
 Rated working current额定工作电流:9.0A

Other Specification/其它规格:


Contact PIN/接触体 : Gold plated Tin bronze/锡青铜镀金
 Housing Material/外壳材质 : PEEK
 Other Shell Material/其它壳体材质: 铜镀镍
 Insulator material/绝缘体材料: PEEK
 IP Rating/防护等级 : IP50

*ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘制
--------	------------------	---------	-------------



Socket front view
插座前视图




view K
K向孔位排列

DRAWN BY:
绘图:PD03 2024.05.28
 CHECKED BY:
审核:Z01 2024.05.28
 APPROVED BY:
核准:PD05 2024.05.28



美易连电子科技(深圳)有限公司
 Meiyilian electronic technology(shenzhen)Co.,Ltd.

GENERAL TOLERANCE
(UNLESS SPECIFIED)
 \leq 10 \pm 0.1
 $<10^\circ \leq 20^\circ$ \pm 0.15
 $>20^\circ \leq 50^\circ$ \pm 0.3
 Angle \pm 1°



FIRST ANGLE PROJECTION

单位 UNIT: mm	名称 PART NAME	DHA-3BP浮动式插座(不带护套式尾帽) DHA-3BP Floating socket (without jacketed tail cap)
比例 SCALE: 1:1		
型号 SIZE: A4	型号 PART NAME	DHA. 3BP. 312. KWKL082
REV/版本 A1		

SHEET: 1 OF 1