

<p>1) Product main performance/产品主要性能指标:</p> <p>Operating Temperature/工作温度: -55℃~200℃  Humidity(max)/最大潮湿: &lt;=95% [at 60 deg C / 140 F]  Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)  Salt Spray Corrosion/盐雾: 96hr  P op (max)/最大环境压力: 60 bar (870 psi)</p> <p>Mechanical data/机械特性:  Vibration/振动: 15g[10Hz~2000Hz]  Shock Resistance/冲击: 100g[6ms]  Endurance (Shell)/机械寿命: 5000次</p> <p>2. 电气性能</p> <p>Insert Configuration/针芯配置: 2T, 318 18Low Voltage  Pin Size/接触件直径: <math>\phi 0.7</math>mm  Contact resistance接触电阻: <math>\leq 12.5</math>m<math>\Omega</math>  Insulation resistance/绝缘电阻: 5000M<math>\Omega</math> (测试电压500V (DC))  Withstand voltage/耐电压: 875V (AC)  Rated working current 额定工作电流: 5.5A  L (mm): 3.6mm</p> <p>Other Specification/其它规格:  Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金  Housing Material/外壳材质: Chrome plated brass/铜镀珍珠铬  Other metal spare parts/其余金属件: Nickel plated brass/铜镀镍  Insulator material/绝缘材料: PPS  IP Rating/防护等级: IP68(插合状态)  *ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.</p>		<p>Mark point 标识点</p>																			
	<p>Panel cut-outs 建议安装开孔尺寸</p>	<p>Mark point 标识点</p> <p>view K K向孔位排列</p>																			
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">DRAWN BY: 2024.6.20</td> <td rowspan="4" style="width: 20%; text-align: center;"> <p>美易连电子科技(深圳)有限公司 MeiYiLian electronic technology (shenzhen) Co. Ltd.</p> </td> <td style="width: 20%;">PART NAME</td> <td style="width: 40%;">2T-ZE固定式插座</td> </tr> <tr> <td>DESIGNED BY: 2024.6.20</td> <td>SCALE: 1:1</td> <td>2T-ZE Fixed socket</td> </tr> <tr> <td>APPROVED BY: 2024.6.20</td> <td>SIZE: A4</td> <td>型号</td> <td>ZEG, 2T, 318, CLN</td> </tr> <tr> <td>标准: 19030</td> <td>PLUST ANGLE: 90DEGREE</td> <td>PART NAME</td> <td></td> </tr> <tr> <td colspan="2"> <p>GENERAL TOLERANCE (UNLESS SPECIFIED):</p> <p>&lt;math&gt;0.10 \pm 0.1&lt;/math&gt;  &lt;math&gt;0.15 \pm 0.15&lt;/math&gt;  &lt;math&gt;0.20 \pm 0.2&lt;/math&gt;  &lt;math&gt;0.30 \pm 0.3&lt;/math&gt;  &lt;math&gt;0.50 \pm 0.5&lt;/math&gt;</p> </td> <td>REV/版本: A1</td> <td>30027: 1 OF 1</td> </tr> </table>		DRAWN BY: 2024.6.20	<p>美易连电子科技(深圳)有限公司 MeiYiLian electronic technology (shenzhen) Co. Ltd.</p>	PART NAME	2T-ZE固定式插座	DESIGNED BY: 2024.6.20	SCALE: 1:1	2T-ZE Fixed socket	APPROVED BY: 2024.6.20	SIZE: A4	型号	ZEG, 2T, 318, CLN	标准: 19030	PLUST ANGLE: 90DEGREE	PART NAME		<p>GENERAL TOLERANCE (UNLESS SPECIFIED):</p> <p>&lt;math&gt;0.10 \pm 0.1&lt;/math&gt;  &lt;math&gt;0.15 \pm 0.15&lt;/math&gt;  &lt;math&gt;0.20 \pm 0.2&lt;/math&gt;  &lt;math&gt;0.30 \pm 0.3&lt;/math&gt;  &lt;math&gt;0.50 \pm 0.5&lt;/math&gt;</p>		REV/版本: A1	30027: 1 OF 1
DRAWN BY: 2024.6.20	<p>美易连电子科技(深圳)有限公司 MeiYiLian electronic technology (shenzhen) Co. Ltd.</p>	PART NAME	2T-ZE固定式插座																		
DESIGNED BY: 2024.6.20		SCALE: 1:1	2T-ZE Fixed socket																		
APPROVED BY: 2024.6.20		SIZE: A4	型号		ZEG, 2T, 318, CLN																
标准: 19030		PLUST ANGLE: 90DEGREE	PART NAME																		
<p>GENERAL TOLERANCE (UNLESS SPECIFIED):</p> <p>&lt;math&gt;0.10 \pm 0.1&lt;/math&gt;  &lt;math&gt;0.15 \pm 0.15&lt;/math&gt;  &lt;math&gt;0.20 \pm 0.2&lt;/math&gt;  &lt;math&gt;0.30 \pm 0.3&lt;/math&gt;  &lt;math&gt;0.50 \pm 0.5&lt;/math&gt;</p>		REV/版本: A1	30027: 1 OF 1																		

