

# 1. Product main performance/产品主要性能指标:

Operating Temperature/工作温度: -55°C~150°C  
 Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F]  
 Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)  
 Salt Spray Corrosion/盐雾: 96hr

## Mechanical data/机械特性:

Vibration/振动: 15g[10Hz~2000Hz]  
 Shock Resistance/冲击: 100g[6ms]  
 Endurance (Shell)/机械寿命: 5000+  
 Cable/配接电缆:  $\phi$ 8.1mm- $\phi$ 9.0mm

## 2. 电气性能



Insert Configuration/针芯配置: 4BP. 320 20Low Voltage  
 Pin Size/接触件直径:  $\phi$ 0.9mm  
 Contact resistance接触电阻:  $\leq$ 9m $\Omega$   
 Insulation resistance/绝缘电阻: 5000M $\Omega$  (测试电压500V(DC))  
 Withstand voltage/耐电压: 1350V(AC)  
 Rated working current额定工作电流: 8.0A

## Other Specification/其它规格:


Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金  
 Housing Material/外壳材质: PEEK  
 Other Shell Material/其它壳体材质: 铜镀镍  
 Insulator material/绝缘体材料: PPS  
 IP Rating/防护等级: IP50

\*ALL MATERIALS ARE ROHS COMPLIANT/所有材料均符合RoHS要求.

REV/版本	DESCRIPTION/变更内容	DATE/日期	DRAWN BY/绘图



Plug front view  
插头前视图




view K  
K向孔位排列

DRAWN BY:  
绘图: PDD3 2024.05.28  
 CHECKED BY:  
审核: ZOI 2024.05.28  
 APPROVED BY:  
核准: PDD5 2024.05.28



美易连电子科技(深圳)有限公司  
 Meiyilian electronic technology (shenzhen) Co., Ltd.

GENERAL TOLERANCE  
(UNLESS SPECIFIED)  
 $\leq$ 10  $\pm$ 0.1  
 $<10^{\circ}$   $\leq$ 20  $\pm$ 0.15  
 $<20^{\circ}$   $\leq$ 50  $\pm$ 0.3  
 Angle  $\pm$ 1 $^{\circ}$



FIRST ANGLE PROJECTION

单位  
UNIT: mm  
 名称  
SCALE: 1:1

比例  
SCALE: 1:1

名称  
PART NAME

TG-4BP 直式插头 (带护套式尾帽)  
 TG-4BP Straight Plug  
 (with jacketed tail cap)

型号  
PART NAME

TGG.4BP.320.KWLAD92Z

REV/版本 A1

SHEET: 1 OF 1