

<p>1) Product main performance/产品主要性能指标:</p> <p>Operating Temperature/工作温度: -55℃~200℃ Humidity(max)/最大潮湿: <=95% [at 60 deg C / 140 F] Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz) Salt Spray Corrosion/盐雾: 96hr P op (max)/最大环境压力: 60 bar (870 psi)</p> <p>Mechanical data/机械特性: Vibration/振动: 15g[10Hz~2000Hz] Shock Resistance/冲击: 100g[6ms] Endurance (Shell)/机械寿命: 5000次</p> <p>2. 电气性能</p> <p>Insert Configuration/针芯配置: 2T, 310 10Low Voltage Pin Size/接触件直径: $\phi 0.9$mm Contact resistance接触电阻: ≤ 9mΩ Insulation resistance/绝缘电阻: 5000MΩ (测试电压500V(DC)) Withstand voltage/耐电压: 1000V(AC) Rated working current额定工作电流: 8.0A L(mm): 3.6mm</p> <p>Other Specification/其它规格: Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金 Housing Material/外壳材质: Chrome plated brass/铜镀珍珠铬 Other metal spare parts/其余金属件: Nickel plated brass/铜镀镍 Insulator material/绝缘材料: PPS IP Rating/防护等级: IP68(插合状态) *ALL MATERIALS ARE RoHS COMPLIANT/所有材料符合RoHS要求.</p>		<p>Mark point 标识点</p> <p>view K K向孔位排列</p>																																								
			<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">DRAWN BY: 高翔/201</td> <td style="width: 15%;">2021.6.20</td> <td rowspan="2" style="width: 15%; text-align: center;"></td> <td colspan="2" style="text-align: center;">美易连电子科技(深圳)有限公司</td> </tr> <tr> <td>DESIGNED BY: 邱彬/201</td> <td>2021.6.20</td> <td colspan="2" style="text-align: center;">Meiyilian electronic technology (shenzhen) Co., Ltd.</td> </tr> <tr> <td>APPROVED BY: 陈永/201</td> <td>2021.6.20</td> <td rowspan="2" style="text-align: center;"></td> <td style="width: 15%;">名称</td> <td>2T-ZE固定式插座</td> </tr> <tr> <td>GENERAL DIMENSION (UNLESS SPECIFIED)</td> <td>UNIT: mm</td> <td>比例</td> <td>1:1</td> <td>2T-ZE Fixed socket</td> </tr> <tr> <td>MIN: -0.1</td> <td>MAX: 0.1</td> <td>材料</td> <td>黄铜</td> <td></td> </tr> <tr> <td>10° ~ 20° ±0.15</td> <td>20° ~ 30° ±0.2</td> <td>规格</td> <td>2T, 310, CLN</td> <td></td> </tr> <tr> <td>30° ~ 45° ±0.2</td> <td>45° ~ 60° ±0.2</td> <td>图号</td> <td></td> <td></td> </tr> <tr> <td>REV/版本</td> <td>1/1</td> <td>数量</td> <td>1</td> <td></td> </tr> </table>	DRAWN BY: 高翔/201	2021.6.20		美易连电子科技(深圳)有限公司		DESIGNED BY: 邱彬/201	2021.6.20	Meiyilian electronic technology (shenzhen) Co., Ltd.		APPROVED BY: 陈永/201	2021.6.20		名称	2T-ZE固定式插座	GENERAL DIMENSION (UNLESS SPECIFIED)	UNIT: mm	比例	1:1	2T-ZE Fixed socket	MIN: -0.1	MAX: 0.1	材料	黄铜		10° ~ 20° ±0.15	20° ~ 30° ±0.2	规格	2T, 310, CLN		30° ~ 45° ±0.2	45° ~ 60° ±0.2	图号			REV/版本	1/1	数量	1	
DRAWN BY: 高翔/201	2021.6.20		美易连电子科技(深圳)有限公司																																							
DESIGNED BY: 邱彬/201	2021.6.20		Meiyilian electronic technology (shenzhen) Co., Ltd.																																							
APPROVED BY: 陈永/201	2021.6.20		名称	2T-ZE固定式插座																																						
GENERAL DIMENSION (UNLESS SPECIFIED)	UNIT: mm		比例	1:1	2T-ZE Fixed socket																																					
MIN: -0.1	MAX: 0.1	材料	黄铜																																							
10° ~ 20° ±0.15	20° ~ 30° ±0.2	规格	2T, 310, CLN																																							
30° ~ 45° ±0.2	45° ~ 60° ±0.2	图号																																								
REV/版本	1/1	数量	1																																							

PCB cut-outs(A-A)			
2	3	4	5
6	7	8	10
12	14	16	18
19	26	32	