





1	2	3	4	5	6	7	8																		
A	<p>1) Product main performance/产品主要性能指标:</p> <p>Operating Temperature/工作温度: -55℃~200℃  Humidity(max)/最大潮湿: &lt;=95% [at 60 deg C / 140 F]  Shielding /屏蔽性能: 75dB(10MHz) 40dB(1GHz)  Salt Spray Corrosion/盐雾: 96hr  P op (max)/最大环境压力: 60 bar (870 psi)</p> <p>Mechanical data/机械特性:  Vibration/振动: 15g[10Hz~2000Hz]  Shock Resistance/冲击: 100g[6ms]  Endurance (Shell)/机械寿命: 5000次</p>						A																		
B	<p>2. 电气性能</p> <p>Insert Configuration/针芯配置: 2T.308 8Low Voltage  Pin Size/接触件直径: Ø0.9mm  Contact resistance接触电阻: ≤9mΩ  Insulation resistance/绝缘电阻: 5000MΩ (测试电压500V(DC))  Withstand voltage/耐电压: 1000V(AC)  Rated working current额定工作电流: 10.0A  L(mm): 3.6mm</p>						B																		
C	<p>Other Specification/其它规格:</p> <p>Contact PIN/接触体: Gold plated Tin bronze/锡青铜镀金  Housing Material/外壳材质: Chrome plated brass/铜镀珍珠铬  Other metal spare parts/其余金属件: Nickel plated brass/铜镀镍  Insulator material/绝缘材料: PPS  IP Rating/防护等级: IP68(插合状态)  *ALL MATERIALS ARE RoHS COMPLIANT/所有材料均符合RoHS要求.</p>						C																		
D	   						D																		
				<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="font-size: 8px;">                 DRAWN BY: 2024.6.20                  制图: 2024.6.20                  CHECKED BY: 2024.6.20                  审核: 2024.6.20                  APPROVED BY: 2024.6.20                  批准: 2024.6.20             </td> <td style="text-align: center; font-weight: bold; font-size: 10px;">MEIYULIAN</td> <td colspan="2" style="text-align: center;">                 美易连电子科技(深圳)有限公司                  Meiyilian electronic technology (shenzhen) Co., Ltd.             </td> <td style="font-size: 8px;">                 规格                  名称                  物料名称                  型号                  物料名称             </td> <td style="font-size: 8px;">                 2T-ZE固定式插座                  2T-ZE Fixed socket                  ZEG. 2T. 308. CLN             </td> </tr> <tr> <td colspan="2" style="font-size: 8px;">                 图例: 1. 外形图                  1:1                  2. 面板开孔尺寸                  1:1                  3. 针芯规格                  1:1                  4. 针芯规格                  1:1                  5. 针芯规格                  1:1             </td> <td style="font-size: 8px;">                 比例                  比例                  比例                  比例                  比例             </td> <td style="font-size: 8px;">                 比例                  比例                  比例                  比例                  比例             </td> <td style="font-size: 8px;">                 比例                  比例                  比例                  比例                  比例             </td> <td style="font-size: 8px;">                 比例                  比例                  比例                  比例                  比例             </td> </tr> <tr> <td colspan="2" style="font-size: 8px;">REV/版本</td> <td style="font-size: 8px;">A1</td> <td colspan="2" style="font-size: 8px;">2024. 1. 18. 1</td> <td style="font-size: 8px;">1 / 1</td> </tr> </table>				DRAWN BY: 2024.6.20 制图: 2024.6.20 CHECKED BY: 2024.6.20 审核: 2024.6.20 APPROVED BY: 2024.6.20 批准: 2024.6.20	MEIYULIAN	美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.		规格 名称 物料名称 型号 物料名称	2T-ZE固定式插座 2T-ZE Fixed socket ZEG. 2T. 308. CLN	图例: 1. 外形图 1:1 2. 面板开孔尺寸 1:1 3. 针芯规格 1:1 4. 针芯规格 1:1 5. 针芯规格 1:1		比例 比例 比例 比例 比例	比例 比例 比例 比例 比例	比例 比例 比例 比例 比例	比例 比例 比例 比例 比例	REV/版本		A1	2024. 1. 18. 1		1 / 1
DRAWN BY: 2024.6.20 制图: 2024.6.20 CHECKED BY: 2024.6.20 审核: 2024.6.20 APPROVED BY: 2024.6.20 批准: 2024.6.20	MEIYULIAN	美易连电子科技(深圳)有限公司 Meiyilian electronic technology (shenzhen) Co., Ltd.		规格 名称 物料名称 型号 物料名称	2T-ZE固定式插座 2T-ZE Fixed socket ZEG. 2T. 308. CLN																				
图例: 1. 外形图 1:1 2. 面板开孔尺寸 1:1 3. 针芯规格 1:1 4. 针芯规格 1:1 5. 针芯规格 1:1		比例 比例 比例 比例 比例	比例 比例 比例 比例 比例	比例 比例 比例 比例 比例	比例 比例 比例 比例 比例																				
REV/版本		A1	2024. 1. 18. 1		1 / 1																				
1	2	3	4	5	6	7	8																		

PCB cut-outs(A-A)				
2	3	4	5	6